



TECHNICAL DATA SHEET

Product Name:	SAFEMARK MULTI-PRIME S.P ADHESION PRIMER
Coating Type:	Solvent based acrylic
Typical Uses:	A very quick curing primer for improving adhesion between concrete/worn asphalt and thermoplastic, Safemark MMA and Safemark S .B Acrylic line marking products.
Theoretical Coverage:	Spray application: 50 to 60 linear metres @ 100mm width line per litre. Brush or Medium pile roller : 25 to 30 linear metres @ 100 mm width line per litre. Coverage will depend on surface profile and porosity.
Drying Time at 20°C: (will vary with Temperature)	Touch Dry: 10 minutes-Overcoat 10 mins up to 6 Hours
Colour:	Translucent
Packaging:	5 & 20 litre containers.
Shelf Life:	Up to 3 years when unopened in good storage conditions.
Storage:	Can be stored for a period of up to 3 years in its original packaging if not opened. Avoid storing in hot, humid or low temperature conditions (freezing). Maximum temperature 35°.
Surface Preparation	Ensure that surface to be coated is dry and free from oil, dust, road salts and other contaminants before application.

Application to concrete:

Stir well and apply with a solvent resistant medium roller, brush or by airless spray. Allow to dry before applying Safemark Solvent based acrylic paint.
New porous concrete should be allowed to cure for one month prior to application.

Health & Safety:

Please see relevant MSDS sheet

