

S.P. Primer for Thermo plastic and S.B. Acrylic

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830
Date of issue: 6/23/2015 Revision date: 11/28/2018 Supersedes: 5/3/2017 Version: 2.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : S.P. Primer for Thermo plastic and S.B. Acrylic

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Industrial/Professional use spec : For professional use only

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

RoadCraft Safety Products Ltd
Unit 1, Knightcott Industrial Estate
Banwell, Weston-Super-Mare
BS29 6JN North Somerset
T 01934 825850 - F 01934 823106
sales@roadcraft.com - www.roadstuds.co.uk | www.hotlineroadmarkings.co.uk | www.roadcraft-paint.co.uk

1.4. Emergency telephone number

Country	Organisation/Company	Address	Emergency number	Comment
United Kingdom	National Poisons Information Service (Belfast Centre) Royal Victoria Hospital	Grosvenor Road BT12 6BA Belfast	0344 892 0111	
United Kingdom	National Poisons Information Service (Birmingham Centre) City Hospital	Dudley Road B18 7QH Birmingham	0344 892 0111	
United Kingdom	National Poisons Information Service (Cardiff Centre) Gwenwyn Ward, Llandough Hospital	Penarth CF64 2XX Cardiff	0344 892 0111	
United Kingdom	National Poisons Information Service Edinburgh Royal Infirmary of Edinburgh	Little France Crescent EH16 4SA Edinburgh	0344 892 0111	
United Kingdom	Guy's & St Thomas' Poisons Unit Medical Toxicology Unit, Guy's & St Thomas' Hospital Trust	Avonley Road SE14 5ER London	0870 243 2241	
United Kingdom	National Poisons Information Service (Newcastle Centre) Regional Drugs and Therapeutics Centre, Wolfson Unit	Claremont Place Newcastle-upon-Tyne NE1 4LP Newcastle	0344 892 0111	

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flammable liquids, Category 2 H225
Serious eye damage/eye irritation, Category 2 H319
Specific target organ toxicity — Single exposure, Category 3, Narcosis H336
Full text of H statements : see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS02

GHS07

S.P. Primer for Thermo plastic and S.B. Acrylic

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Signal word (CLP)	: Danger
Hazardous ingredients	: acetone, propan-2-one, propanone; ethyl acetate; n-butyl acetate
Hazard statements (CLP)	: H225 - Highly flammable liquid and vapour. H319 - Causes serious eye irritation. H336 - May cause drowsiness or dizziness.
Precautionary statements (CLP)	: P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P233 - Keep container tightly closed. P280 - Wear protective gloves, eye protection, protective clothing. P312 - Call a doctor if you feel unwell. P337+P313 - If eye irritation persists: Get medical advice/attention. P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.
EUH-statements	: EUH066 - Repeated exposure may cause skin dryness or cracking.

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
acetone, propan-2-one, propanone	(CAS-No.) 67-64-1 (EC-No.) 200-662-2 (EC Index-No.) 606-001-00-8	50 - 100	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
ethyl acetate	(CAS-No.) 141-78-6 (EC-No.) 205-500-4 (EC Index-No.) 607-022-00-5	10 - 20	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Call a poison center or a doctor if you feel unwell. If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Do NOT induce vomiting. If swallowed, seek medical advice immediately and show this container or label.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	: May cause drowsiness or dizziness.
Symptoms/effects after skin contact	: Repeated exposure may cause skin dryness or cracking.
Symptoms/effects after eye contact	: May cause severe irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Highly flammable liquid and vapour.
Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

S.P. Primer for Thermo plastic and S.B. Acrylic

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid contact with skin and eyes. Avoid inhalation of product.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.

Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapours may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Use only outdoors or in a well-ventilated area. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes.

Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Ground/bond container and receiving equipment.

Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

acetone, propan-2-one, propanone (67-64-1)

DNEL/DMEL (Workers)

Acute - local effects, inhalation	2420 mg/m ³
Long-term - systemic effects, dermal	186 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	1210 mg/m ³

ethyl acetate (141-78-6)

DNEL/DMEL (Workers)

Acute - systemic effects, inhalation	1468 mg/m ³
Acute - local effects, inhalation	1468 mg/m ³
Long-term - systemic effects, dermal	63 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	734 mg/m ³
Long-term - local effects, inhalation	734 mg/m ³

n-butyl acetate (123-86-4)

DNEL/DMEL (Workers)

Acute - systemic effects, inhalation	960 mg/m ³
Acute - local effects, inhalation	960 mg/m ³
Long-term - systemic effects, inhalation	480 mg/m ³
Long-term - local effects, inhalation	480 mg/m ³

S.P. Primer for Thermo plastic and S.B. Acrylic

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

8.2. Exposure controls

Appropriate engineering controls:

Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction.

Materials for protective clothing:

Wear overalls or long sleeved shirt. (EN 467). Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Hand protection:

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals. The breakthrough time must be greater than the end use time of the product. The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed. Gloves should be replaced regularly and if there is any sign of damage to the glove material. Always ensure that gloves are free from defects and that they are stored and used correctly. The performance or effectiveness of the glove may be reduced by physical/chemical damage and poor maintenance. Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred. For prolonged or repeated handling, use the following type of gloves: Recommended: > 30 minutes (breakthrough time): Latex B2. The recommendation for the type or types of glove to use when handling this product is based on information from the following source: EN 374-3 : 2003. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

Eye protection:

Safety glasses with side shields. (EN166)

Skin and body protection:

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Respiratory protection:

Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Recommended: organic vapour (Type A) and particulate filter (EN 140).

Environmental exposure controls:

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Colourless.
Odour	: characteristic.
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: No data available
Flash point	: -17 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Not applicable
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density	: ≈ 0.88 g/ml (20°C)
Solubility	: No data available
Log Pow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

9.2. Other information

VOC content : ≈ 620 g/l

S.P. Primer for Thermo plastic and S.B. Acrylic

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 10: Stability and reactivity

10.1. Reactivity

Highly flammable liquid and vapour.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified

Acute toxicity (dermal) : Not classified

Acute toxicity (inhalation) : Not classified

acetone, propan-2-one, propanone (67-64-1)

LD50 oral rat	5800 mg/kg
LD50 dermal rabbit	> 15800 mg/kg
LC50 inhalation rat (mg/l)	76 mg/l/4h

ethyl acetate (141-78-6)

LD50 oral rat	5620 ml/kg
LD50 dermal rabbit	> 20000 mg/kg
LC50 inhalation rat (mg/l)	1600 mg/l

Skin corrosion/irritation : No data available

Serious eye damage/irritation : Causes serious eye irritation.

Respiratory or skin sensitisation : No data available

Germ cell mutagenicity : No data available

Carcinogenicity : No data available

Reproductive toxicity : No data available

STOT-single exposure : May cause drowsiness or dizziness.

STOT-repeated exposure : Not classified

Aspiration hazard : No data available

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.

Acute aquatic toxicity : Not classified

Chronic aquatic toxicity : Not classified

acetone, propan-2-one, propanone (67-64-1)

LC50 fish 1	5540 mg/l Oncorhynchus Mykiss
EC50 Daphnia 1	8800 mg/l Daphnia Magna

ethyl acetate (141-78-6)

LC50 fish 1	230 mg/l Pimpephales Promelas
EC50 Daphnia 1	165 mg/l Daphnia Magna

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

S.P. Primer for Thermo plastic and S.B. Acrylic

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional legislation (waste)	: Disposal must be done according to official regulations.
Waste treatment methods	: The generation of waste should be avoided or minimized wherever possible. Significant quantities of waste product residues should not be disposed of via foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.
Sewage disposal recommendations	: The generation of waste should be avoided or minimized whenever possible. Waste packaging should be recycled; Incineration or landfill should only be considered when recycling is not feasible. This material and his container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
Product/Packaging disposal recommendations	: The European Waste Catalogue classification of this product, when disposed of as waste is 08 0111: waste paint and varnish containing organic solvents or other dangerous substances.
Additional information	: Flammable vapours may accumulate in the container.
Ecology - waste materials	: This product is regarded as hazardous waste as defined by EU Directive 91/689/EEC.

SECTION 14: Transport information

In accordance with ADR / IATA / IMDG

14.1. UN number

UN-No. (ADR)	: 1866
UN-No. (IMDG)	: 1866
UN-No. (IATA)	: 1866

14.2. UN proper shipping name

Proper Shipping Name (ADR)	: RESIN SOLUTION
Proper Shipping Name (IMDG)	: RESIN SOLUTION
Proper Shipping Name (IATA)	: Resin solution
Transport document description (ADR)	: UN 1866 RESIN SOLUTION, 3, II, (D/E)
Transport document description (IMDG)	: UN 1866 RESIN SOLUTION, 3, II
Transport document description (IATA)	: UN 1866 Resin solution, 3, II

14.3. Transport hazard class(es)

ADR

Transport hazard class(es) (ADR)	: 3
Danger labels (ADR)	: 3



IMDG

Transport hazard class(es) (IMDG)	: 3
Danger labels (IMDG)	: 3



IATA

Transport hazard class(es) (IATA)	: 3
Hazard labels (IATA)	: 3

S.P. Primer for Thermo plastic and S.B. Acrylic

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830



14.4. Packing group

Packing group (ADR)	: II
Packing group (IMDG)	: II
Packing group (IATA)	: II

14.5. Environmental hazards

Dangerous for the environment	: No
Marine pollutant	: No
Other information	: No supplementary information available

14.6. Special precautions for user

Overland transport

Classification code (ADR)	: F1
Special provisions (ADR)	: 640D
Limited quantities (ADR)	: 5I
Excepted quantities (ADR)	: E2
Packing instructions (ADR)	: P001, IBC02, R001
Special packing provisions (ADR)	: PP1
Mixed packing provisions (ADR)	: MP19
Portable tank and bulk container instructions (ADR)	: T4
Portable tank and bulk container special provisions (ADR)	: TP1, TP8
Tank code (ADR)	: LGBF
Vehicle for tank carriage	: FL
Transport category (ADR)	: 2
Special provisions for carriage - Operation (ADR)	: S2, S20
Hazard identification number (Kemler No.)	: 33
Orange plates	:



Tunnel restriction code (ADR)	: D/E
EAC code	: •3YE

Transport by sea

Limited quantities (IMDG)	: 5 L
Excepted quantities (IMDG)	: E2
Packing instructions (IMDG)	: P001
Special packing provisions (IMDG)	: PP1
IBC packing instructions (IMDG)	: IBC02
Tank instructions (IMDG)	: T4
Tank special provisions (IMDG)	: TP1, TP8
EmS-No. (Fire)	: F-E
EmS-No. (Spillage)	: S-E
Stowage category (IMDG)	: B

Air transport

PCA Excepted quantities (IATA)	: E2
PCA Limited quantities (IATA)	: Y341
PCA limited quantity max net quantity (IATA)	: 1L
PCA packing instructions (IATA)	: 353
PCA max net quantity (IATA)	: 5L
CAO packing instructions (IATA)	: 364
CAO max net quantity (IATA)	: 60L
Special provisions (IATA)	: A3
ERG code (IATA)	: 3L

S.P. Primer for Thermo plastic and S.B. Acrylic

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

VOC content : \approx 620 g/l

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Full text of H- and EUH-statements:

Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 2	Flammable liquids, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
H225	Highly flammable liquid and vapour
H319	Causes serious eye irritation
H336	May cause drowsiness or dizziness
EUH066	Repeated exposure may cause skin dryness or cracking

SDS EU (REACH Annex II)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product